





| Dimensions | |
|---|------------|
| Width (external) | 1398.00 mm |
| Depth (external) | 615.00 mm |
| Height (external) | 2050.00 mm |
| Width (internal) | 1245.00 mm |
| Depth (internal) | 400.00 mm |
| Height (internal) | 1858.00 mm |
| The available internal dimensions can vary depending on the interior equipment package. | |

| Weight / Load | |
|-----------------------------------|--------------|
| Weight without interior equipment | 690 kg |
| Distributed load | 571.00 kg/m² |
| Maximum load | 600 kg |

| 75 DN |
|----------|
| 9 m³/h |
| 111 m³/h |
| 72 |
| |

For further details of the lead-through possibilities and exhaust air please have a closer look to EN 14470-2.

| Colouring / Surface finish | |
|------------------------------|------------|
| Body colour code | RAL 7035 |
| Body colour | Light grey |
| Body surface finish | plain |
| Door / Drawer colour code | RAL 7035 |
| Door / Drawer colour | Light grey |
| Door / Drawer surface finish | plain |

| General Information | |
|--------------------------|----------|
| x 50-litre gas cylinders | 4 piece |
| Door opening angle | 180.00 |
| Depth with open doors | 1337 mm |
| Customs tariff number | 94032080 |















Gas cylinder cabinet G-ULTIMATE-90 Model G90.205.140, in light grey (RAL 7035)

Safe and approved storage of flammable or toxic gases in working areas – for up to 4 x 50-litre gas cylinders

Function / construction:

- No unauthorised use: doors lockable with profile cylinder (integration in an existing locking system possible)
- easy alignment: adjusting aids to compensate for uneven floor
- easy mounting of connecting pipes and gas fittings: large interior height (1890 mm), many lead-through possibilities on the top of the cabinet
- **ventilation:** integrated air ducts ready for connection (DN 75) to a technical exhaust, even ventilation inside the cabinet
- **tested and certified:** according to the stricter GS principles

Available equipment:

- Comfort interior equipment complete with mounting rails, rolling ramp (L = 350 mm) with pneumatic damper, cylinder retainer and matching tension belts
- standard interior equipment complete with mounting rails, rolling ramp, cylinder retainer and matching tension belts
- cylinder retainer variable installation in the cabinet, flexibly adjustable in depth, across the entire width of the cabinet
- sateral cylinder retainer for two 10-litre cylinders, alternatively in height adjustable version (no tools required)







